

# MyPBX SOHO

Integriran Hibridni IP-PBX za mala preduzeća



IVR



Conference



RingGroup



Queue



Voicemail



PIN User



Firewall



QoS



VLAN



DDNS

MyPBX SOHO je samostalan nadogradiv hibridni PBX specijalno dizajniran za mala preduzeća i kancelarije sa do 32 korisnika koji omogućava fleksibilnost integracije ISDN, PSTN linija, i VoIP linija. Na ovaj način, troškovi komunikacije preduzeća su znatno umanjeni korišćenjem najnovijih VoIP tehnologija dok je tradicionalna pouzdanost zagarantovana.

- **Jednostavan za upotrebu**

Jednostavan za razvoj i upravljanje preko web baziranog interfejsa

- **Robusne sve-u-jednom funkcije**

Pruža kompanijsku klasu komunikacijskih funkcija malim i srednjim preduzećima

- **Modularna tehnologija**

Prilagodljiva kombinacija FXO, FXS, BRI, modula

- **Izaberite svoj IP telefon**

Savršena interoperabilnost sa svim aktuelnim IP telefonima

- **Govori vašim jezikom(uskoro)**

Višejezični web GUI i glasovno navođenje

- **Nema dodatnih troškova licenciranja**

Skalabilan sa "prikluči i koristi" jednostavnošću bez licenciranja

- **Poboljšana sigurnost**

Osigurava Vašu komunikaciju od napada i zloupotreba pomoću firewall-a.

- **Ušteda energije**

Integriran system sa niskom potrošnjom struje za vašu "zelenu" kancelariju



## PBX Funkcije

- Automated Attendant (IVR)
- Attended Transfer
- Blind Transfer
- Blacklist
- Call Back
- Call Detail Records (CDR)
- Call Forward
- Call Parking
- Call Pickup
- Call Routing
- Call Waiting
- Caller ID
- Conference
- Do Not Disturb (DND)
- Follow me
- Intercom/Zone Intercom
- Music on Hold
- Music on Transfer
- Queue
- Ring Group
- Skype Integration (Skype Connect)
- Speed Dial
- Voicemail (3000 minutes)
- Voicemail to email
- Voicemail Forwarding

## Napredne funkcije

- Dial by Name
- Direct Inward System Access (DISA)
- Distinctive Ringtone
- LDAP Server
- Mobility Extension
- One Touch Recording
- Phone Provisioning for Aastra, Cisco, Escene, Fanvil, Grandstream, Htek, Panasonic, Polycom, Snom, Yealink IP Phones

- QoS (voice quality)
- Route by Caller ID
- Spy functions (Normal Spy, Whisper Spy, Barge Spy)
- Static Route

## Hardverski interfejs

- LAN Ethernet 10/100 BASE-T
- WAN Ethernet 10/100 BASE-T
- Do 4 FXO porta
- Do 4 FXS porta
- Do 4 BRI porta

## Kapacitet sistema

- 32 IP telefona/korisnika
- 15 istovremenih poziva
- 512 MB Fleš memorije
- 256 MB RAM memorije

## Procesuiranje Glasa

- Protokol: SIP (RFC3261), IAX2
- Transport: UDP, TCP, TLS, SRTP
- DTMF: RFC2833, SIP INFO, In-band
- Kodek: G.711 (a-law, u-law), G.722, G.726, G.729 A, GSM, Speex, ADPCM, H261, H263, H263p, H264, MPEG4

## Više jezika

- Govorne poruke sistema: American English, Australian English, British English, Afrikaans, Arabic, Chinese, Dutch, French, Canadian French, Danish, Finnish, German, Greek, Hebrew, Hungarian, Italian, Korean, Norwegian, Persian, Polish, Portuguese, Brazilian Portuguese, Russian, Spanish, Latin American Spanish, Mexican Spanish, Thai, Turkish,

Swedish

- Web GUI: English, Chinese Simplified, Chinese traditional, Portuguese, Spanish, Russian, Hebrew, Turkish, French, Italian, Polish, Romanian, Albanian, Thai, Korean, Persian, German, Dutch, Croatia

## Bezbednost

- Firewall
- SIP TLS transport
- SRTP (RTP encryption)

## Faksevi

- T30, T38 faxes
- Fax to Email
- Incoming fax tone detection

## Internet

- DHCP Server
- DDNS
- Static IP
- DHCP Client
- PPPoE
- VLAN
- VPN: OpenVPN, L2TP, IP Sec

## Fizičke karakteristike

- Dimenzije: 160x160x30 mm
- Težina: 500 g
- Napajanje: AC 100-240V (DC 12V, 1A)
- Radna temperatura: 0 do 40°C, 32 do 104°F
- Temperatura skladištenja: -20 do 65°C, -4 do 149°F
- Vlažnost: 10-90%  
Bez kondenzacije