

MyPBX Standard

Integrisan Hibridni IP-PBX za mala preduzeća



IVR



Conference



RingGroup



Queue



Voicemail



PIN User



Firewall



QoS



VLAN



DDNS

MyPBX Standard je samostalan nadogradiv hibridni PBX specijalno dizajniran za mala preduzeća i kancelarije sa do 100 korisnika koji omogućava fleksibilnost integracije ISDN, PSTN, i VoIP/GSM/UMTS linija. Na ovaj način, troškovi komunikacije preduzeća su znatno umanjeni korišćenjem najnovijih VoIP tehnologija dok je tradicionalna pouzdanost zagarantovana.

- **Jednostavan za upotrebu**
Jednostavan za razvoj i upravljanje preko web baziranog interfejsa
- **Robusne sve-u-jednom funkcije**
Pruža kompanijsku klasu komunikacijskih funkcija malim i srednjim preduzećima
- **Modularna tehnologija**
Prilagodljiva kombinacija FXO, FXS, BRI, GSM, CDMA, UMTS modula
- **Izaberite svoj IP telefon**
Savršena interoperabilnost sa svim aktuelnim IP telefonima
- **Govori vašim jezikom(uskoro)**
Višejezični web GUI i glasovno navođenje
- **Nema dodatnih troškova licenciranja**
Skalabilan sa "prikluči i koristi" jednostavnošću bez licenciranja
- **Poboljšana sigurnost**
Osigurava Vašu komunikaciju od napada i zloupotreba pomoću firewall-a.
- **Ušteda energije**
Integrisan sistem sa niskom potrošnjom struje za vašu "zelenu" kancelariju



PBX Funkcije

- Automated Attendant (IVR)
- Attended Transfer
- Blind Transfer
- Blacklist
- Call Back
- Call Detail Records (CDR)
- Call Forward
- Call Parking
- Call Pickup
- Call Routing
- Call Waiting
- Caller ID
- Conference
- Do Not Disturb (DND)
- Follow me
- Intercom/Zone Intercom
- Music on Hold
- Music on Transfer
- Queue
- Ring Group
- Skype Integration (Skype Connect)
- Speed Dial
- Voicemail (3000 minutes)
- Voicemail to email
- Voicemail Forwarding

Napredne funkcije

- Dial by Name
- Direct Inward System Access (DISA)
- Distinctive Ringtone
- Email to SMS
- SMS to Email
- LDAP Server
- Mobility Extension
- One Touch Recording
- Phone Provisioning for Aastra, Cisco, Escene, Fanvil, Grandstream, Htek, Panasonic, Polycom, Snom, Yealink IP Phones
- QoS (voice quality)

- Route by Caller ID
- Spy Functions
- Static Route

Hardverski interfejs

- 1 LAN Ethernet 10/100 BASE-T
- 1 WAN Ethernet 10/100 BASE-T
- Do 16 FXO porta
- Do 16 FXS porta
- Do 8 BRI porta (pomoću B2 modula)
- Do 8 GSM porta
- Do 8 UMTS porta
- Do 8 CDMA porta
- 1 USB port (2.0)

Kapacitet sistema

- 100 IP telefona/korisnika
- 25 istovremenih poziva
- 512 MB Fleš memorije
- 512 MB RAM memorije

Procesuiranje glasa

- Protokol: SIP (RFC3261), IAX2
- Transport: UDP, TCP, TLS, SRTP
- DTMF: RFC2833, SIP INFO, In-band
- Kodek: G.711 (a-law, u-law), G.722, G.726, G.729 A, GSM, Speex, ADPCM, H261, H263, H263p, H264, MPEG4

Više jezika

- Govorne poruke sistema: American English, Australian English, British English, Afrikaans, Arabic, Chinese, Dutch, French, Canadian French, Danish, Finnish, German, Greek, Hebrew, Hungarian, Italian, Korean, Norwegian, Persian, Polish, Portuguese, Brazilian Portuguese, Russian, Spanish, Latin American Spanish, Mexican Spanish, Thai,

- Turkish, Swedish
- Web GUI: English, Chinese Simplified, Chinese traditional, Portuguese, Spanish, Russian, Hebrew, Turkish, French, Italian, Polish, Romanian, Albanian, Thai, Korean, Persian, German, Dutch, Croatia

Bezbednost

- Firewall
- SIP TLS transport
- SRTP (RTP encryption)

Faksevi

- T30, T38 faxes
- Fax to Email
- Incoming fax tone detection

Internet

- DHCP Server
- DDNS
- Static IP
- DHCP Client
- VLAN
- VPN: OpenVPN, L2TP, IP Sec

Fizičke karakteristike

- Dimenzije: 290x180x33 mm
- Težina: 700 g
- Napajanje: AC 100-240V (DC 12V 5A)
- Radna temperatura: 0 to 40°C, 32 to 104°F
- Temperatura skladištenja: -20 to 65°C, -4 to 149°F
- Vlažnost: 10-90%
Bez kondenzacije